


Sidus Single Board Computer (SSBC)

High Performance On-board Computer



The Sidus Single Board Computer (SSBC) is a rugged, modular 3U VPX solution designed for size-constrained and mission-critical applications and engineered for high-performance computing in extreme environments.

The SSBC is a part of the Fortis™ suite, which includes the following product line options:

- » FeatherEdge™ AI/ML Processor
- » Position, Navigation, and Timing (PNT)
- » Global Positioning System (GPS) Receiver
- » Custom Input/Output (I/O) Card
- » Power Converter Card
- » Software Defined Radio (SDR)

Key Features



- » **High-Performance Processing** - Powered by a Quad-Core ARM® processor delivering 30,000+ DMIPS and 45,000 CoreMarks for compute-intensive tasks
- » **Secure Boot and Scalable Memory** - Features secure QSPI Flash, DDR4 RAM, 64 GB NAND Flash, and 512 GB User Flash with triple watchdogs for enhanced reliability
- » **High-Speed Connectivity** - Supports 10 Gbps SerDes, PCIe® Gen3, Ethernet, UART, and JTAG for fast data transfer and streamlined development
- » **Comprehensive OS Support** - Includes VxWorks BSP with optional support for Linux, PikeOS, and RTEMS to meet diverse mission requirements

Applications



Air

- » Aerial Drones
- » Ballistic Missiles
- » Commercial and Civil Aircraft




Sea

- » Submarines
- » Surface Ships
- » Underwater Drones



Land

- » Command and Control (C2) Network
- » Electronic Warfare (EW)
- » Intelligence, Surveillance, and Reconnaissance (ISR)
- » Unmanned Ground Vehicles (UGVs)



Space

- » Counterspace Operations
- » Satellites
- » Space Defense
- » Space Situational Awareness



NASDAQ | SIDU
SIDUSSPACE.COM
+1 (321) 450.5633

©2025 Sidus Space. All Rights Reserved.

Headquarters and Mission Control Center
150 N Sykes Creek Pkwy, STE 200
Merritt Island, Florida, USA 32953

Satellite Production and Manufacturing Facility
400 West Central Blvd,
Cape Canaveral, Florida, USA 32920



Sidus Single Board Computer (SSBC)

High Performance On-board Computer



Sidus Single Board Computer (SSBC) Specifications

System Architecture	System on Chip (SoC)	Teledyne e2V QLS1046 » High-speed security protocol processing, including IPsec, SSL, TLS, and IKE
	Processor	Quad Core ARM® Cortex®-A72 » 64-bit ARM® Cortex®-A72 (with ECC-protected L1 and L2 cache memories) » RAM 4GB DDR4 with ECC, 72-bit interface, operating @ up to 1050 MHz » Up to 1.8 GHz operation
	FPGA	Rad-hard PolarFire® up to 5 Softcore RISC V Processors (RTOS)
	Board Resources	» Watchdog (x2 SoC internal and x1 SoC external) » Temperature sensors » Voltage sensors

Memory Resources	QSPI Flash	512 MB
	NAND Flash	64 GB
	User Flash	512 GB

I/O	Gigabit Ethernet (10/100/1000Base-T)	3
	10 Gigabit Ethernet (10GbE)	2
	USB 2.0	1
	USB 3.0	1
	Serial Ports (RS422)	2
	1 PPS	1 IN
	I2C	2
	CANbus	1
	PCIe®	1x PCIe® x2 1x PCIe® x1
	Differential Pairs / Single-ended	14 / 28

Software	» Linux OS
	» VxWorks
	» PikeOS
	» RTEMS

Mechanical	Dimensions	3U VPX Slot (100 mm x 160 mm)
	Weight	<1 kg (2.2 lbs)

Power	Input Power	12 VDC and 3.3 VDC
	Power Consumption	» 15-25 W under typical load » Max 50 W when board is fully utilized

Environmental	Cooling Method	Conduction-cooled	
	Operating Temp	Min.	-55° C
		Max.	+125° C
	Vibration (3 Axes)	0.024G / 25 Hz	
		MIL-STD-810H	
		0.15G / 1 kHz	
	Random (Freq)	0.02G / 0-2 kHz	
	Sine (Freq)	10G / 0-500 Hz	
Shock (3 Axes)	20G / 5 mS		

Orbit Type	Terrestrial	LEO	GEO
Radiation Tolerance (TID)	N/A	25 krad	100 krad
Latch Up Immunity (SEL/SEE)	N/A	>40 MeV-cm²/mg	>75 MeV-cm²/mg
Relative Humidity	0-95%	N/A	N/A
Part Selection	MIL-SPEC	Rad-hard	Rad-hard
SEU Rate	N/A	<2.56 × 10 ⁻⁵ NA	<2.56 × 10 ⁻⁵ NA



NASDAQ | SIDU
SIDUSSPACE.COM
+1 (321) 450.5633

©2025 Sidus Space. All Rights Reserved.

Headquarters and Mission Control Center
150 N Sykes Creek Pkwy, STE 200
Merritt Island, Florida, USA 32953

Satellite Production and Manufacturing Facility
400 West Central Blvd,
Cape Canaveral, Florida, USA 32920

